

# UNITÀ ESTERNE

COD.	CAPACITÀ Btu Hi/Mi/Lo RAFFR. RISC.	SEER/SCOOP	RUMOROSITÀ dB(A)	TUBAZIONI Ø Liq./Gas.	PESO Kg	
					netto	lordo
X9C1	1700 / 8500 / 11500 1700 / 9554 / 12000	6,1 A++ / 4,0 A+	55	1/4" - 3/8"	29,5	32
X12C1	2047 / 10918 / 12965 2047 / 11942 / 12966	6,1 A++ / 4,0 A+	55	1/4" - 3/8"	31	34
X18C1	2218 / 15695 / 17742 2388 / 17742 / 18425	6,1 A++ / 4,0 A+	58	1/4" - 3/8"	34	37
X24C1	6142 / 21000 / 21837 5469 / 22000 / 22519	6,1 A++ / 4,0 A+	59	1/4" - 5/8"	46	50,5
X20C2	7300 / 17742 / 19800 8800 / 18425 / 20200	6,1 A++ / 4,0 A+	55	1/4" - 3/8" 1/4" - 3/8"	43	46
X24C3	7800 / 24229 / 29000 12500 / 29000 / 30000	6,1 A++ / 4,0 A+	55	1/4" - 3/8"	68	73
X28C4	7800 / 27296 / 35000 12500 / 32414 / 35000	6,1 A++ / 4,0 A+	55	1/4" - 3/8"	68	74