

UNITÀ ESTERNE

| COD. | CAPACITÀ Btu Hi/Mi/Lo RAFFR. RISC. | SEER/SCOOP | RUMOROSITÀ dB(A) | TUBAZIONI Ø Liq./Gas. | PESO Kg | |
|-------|---|------------------|---------------------|-----------------------------|---------|-------|
| | | | | | netto | lordo |
| X9C1 | 1700 / 8500 / 11500 1700 / 9554 / 12000 | 6,1 A++ / 4,0 A+ | 55 | 1/4" - 3/8" | 29,5 | 32 |
| X12C1 | 2047 / 10918 / 12965 2047 / 11942 / 12966 | 6,1 A++ / 4,0 A+ | 55 | 1/4" - 3/8" | 31 | 34 |
| X18C1 | 2218 / 15695 / 17742 2388 / 17742 / 18425 | 6,1 A++ / 4,0 A+ | 58 | 1/4" - 3/8" | 34 | 37 |
| X24C1 | 6142 / 21000 / 21837 5469 / 22000 / 22519 | 6,1 A++ / 4,0 A+ | 59 | 1/4" - 5/8" | 46 | 50,5 |
| X20C2 | 7300 / 17742 / 19800 8800 / 18425 / 20200 | 6,1 A++ / 4,0 A+ | 55 | 1/4" - 3/8" 1/4" - 3/8" | 43 | 46 |
| X24C3 | 7800 / 24229 / 29000 12500 / 29000 / 30000 | 6,1 A++ / 4,0 A+ | 55 | 1/4" - 3/8" | 68 | 73 |
| X28C4 | 7800 / 27296 / 35000 12500 / 32414 / 35000 | 6,1 A++ / 4,0 A+ | 55 | 1/4" - 3/8" | 68 | 74 |