



LABEL FOR EXPEDITION BOX

NS Code: 55-1-190-0009
VS Code: -
Description: MANIFOLD 2 VALVES WITH SAFETY VALVE AND GAUGE
INLET: W20x1/14" L.H.
OUTLET: W20x1/14" L.H.

Pcs per carton: 11
Date: 11

IL SACCHETTO D'IMBALLAGGIO NON DEVE ESSERE CHIUSO

PAY ATTENTION TO THE VALVES/MANOMETER ORIENTATION

PERFORMANCE RICHIESTE

TENUTA APPARECCHIO	PERFETTAMENTE A TENUTA A 16 bar: PERDITA < 15 cc/h
PERDITA DI CARICO	< 20 mbar CON PRESSIONE DI 0.3 bar E PORTATA 2 kg/h SU OGNI SINGOLA VALVOLA
APERTURA VDS	17.65 bar ± 5%
ANTIRITORNO VALVOLA	PERDITA < 200 cc/h CON PRESSIONE DA 0.3 bar A 16 bar

NO	NO PRODUCT	DENOMINATION	Q.TY
1	30-1-110-0357	S/A MANIFOLD (2 VALVE)	1
2	04-1-110-0136	GASKET (OMEGA CODE 0461100012)	2
3	34-1-110-0838	INSTRUCTION FOR MANIFOLD	1
4	80-6-190-0012	VALVE FOR ITALIAN MARKET	2
5	16-1-950-0333	S/A SAFETY VALVE FOR MANIFOLD	1
6	23-1-210-0621	PLASTIC BAG FOR MANIFOLD (210x500)	1
7	23-1-510-0020	BOX 1100x800x815	1
8	34-1-210-2137	LABEL FOR EXPEDITION BOX (100X100)	1

	DENOMINATION MANIFOLD (2 VALVE) WITH ACCESSORIES - 0.3-16 bar					
	MODEL RECA	ORIFICE -	INLET W20x1/14" L.H.	OUTLET W 20x1/14" L.H.	SHARED N.A.	PROD. INT. GROUP -
PERFORMANCE DOC. N.A.	COUNTRY N.A.	COUNTRY SPECIFIC N.A.	WEIGHT N.A.	SCALE 1:2	MODIFY FILE DM05166	PRODUCT NO 55-1-190-0009
PROD. EVOLUTION DEFINITIVE	PROJECT NO A103	RELEASE LEVEL APPROVED+	DRAWN BY RUSSO R.	VERIFIED BY TOMASELLI L.	APPROVED BY SCHLICK B.	DATE 17/12/14
						2